




C2062

100kV Single Core Silicone

CONSTRUCTION



KEY

1. CONDUCTOR	#8AWG (133x29) SILVER PLATED COPPER
2. SEMI-CON	SILICONE Ø5.6mm ±0.5mm MIN. WALL
3. DIELECTRIC	SILICONE RUBBER (WHITE) Ø16.5mm ±0.25mm



TECHNICAL INFORMATION

Part Number C2062		
Voltage	kV (DC)	100
	kV(AC)	30
Conductor Size	AWG	8
	mm ²	10
Dielectric Material		SILICONE
Outside Diameter mm		16.5
Impedance (Ohms)		41
Capacitance (pf/m)		164
Min Bend Radius mm		64
Min Ambient Temp	°F	-60
	°C	-51
Max Conductor Temp	°F	392
	°C	200
Weight kg/m		0.37

GLOBAL PRESENCE



UK Office:

Genvolt, New Road, Bridgnorth, Shropshire, WV16 6NN, United Kingdom

Tel: +44 (0) 1746 862 555

Email: info@genvolt.co.uk Website: www.genvolt.com

India Office:

Genvolt India Private Limited

806, Suratwala Mark Plazzo, Hinjewadi Village, Hinjewadi, Pune, Maharashtra - 411057, India

Email: supportindia@genvolt.co.uk Website: www.genvolt.in

Research and Development:

Genvolt Ltd

New road, Bridgnorth, Shropshire, WV16 6NN

Factories:

Genvolt Ltd

New road, Bridgnorth, Shropshire, WV16 6NN

Boher High Voltage Power Supplies Ltd (Genvolt China)

No. 79 Yandangshan Road, Suyu District, Suqian City, Jiangsu, China